



## SEP 60 ST

Compressed air  
Condensate cleaner



**Single-use, quick-fit  
condensate cleaner for compressed air  
systems of up to 1.7 m<sup>3</sup>/min or 11kW**

**Only SEPURA** gives you this performance from such a small package. Our new **STERLING** filter medium gives **SEP 60 ST** the capacity to out-perform separators 3 times its size. And it's pure simplicity to install and replace. Just fix the permanent back plate to a wall or cabinet, insert two push-in fittings and it starts to protect you—and the environment. Oily water in; clean water out. Discharge straight to the sewer (as low as 5ppm oil-in-water) —legally\*

At the end of its service life, remove the push fittings, attach the clip-on lid and plug (provided with the replacement unit) and slide it off the wall plate. Sealed, outwardly clean and ready for disposal.

- Compressor capacity up to 60cfm (1.7 m<sup>3</sup>/min or 11kw).
- Service life - 4000 operating hours at 60cfm or 8000 hours at 30cfm (replace after a maximum of 2 years)\*\*
- Dimensions only 145mm x 145mm x 220mm
- Wall or cabinet mounting (permanent 'quick-fit' plate provided)
- Push-in connections for speed and ease
- Cleanest possible servicing routine
- Clip-on cap and blanking plug seal the retained oil inside the cleaner for transit. ABS plastic and filter material are re-cyclable. Treat as oil-contaminated waste
- Lightweight and compact for international bulk shipping



### SEPURA Technologies Ltd

24 Longford Ind Est, Longford Rd  
Bridgtown, Cannock, Staffordshire, WS11 0DG

tel: +44(0)1543 378402 fax: +44 (0)1543 578202

Email: [sales@sepura-technologies.com](mailto:sales@sepura-technologies.com)

web: [www.sepura-technologies.com](http://www.sepura-technologies.com)



*\*It is the user's responsibility to verify discharge allowances in his/her region*

*\*\*Assumes compressor oil carry-over is no more than 5mg/m<sup>3</sup>*